





LED RANGE PRICE LIST

w.e.f. August 2017



modern workspaces
recessed | page 04



modern workspaces
suspended | page 08



commercial interiors
downlighters | page 12



lighting controls
page 16



cleanroom & sterile areas
page 18



industries
page 20



outdoor
street lighting
page 24



Driven by Efficiency, Leading by Performance

Since its inception, in 1991 Wipro Lighting has always been associated with new product innovations and unique lighting concepts. Be it from high efficiency LED luminaires and lighting management systems for green buildings, we are the leaders in providing comprehensive energy efficient solutions.

Wipro Lighting is at the forefront in providing smart, intelligent & connected LED lighting solutions for various application areas including modern workspaces, industries, retail, healthcare, pharmaceuticals, roads & highways, landscapes and many more.

We have a single minded focus on enhancing competitive advantage and thereby customer profitability at all times and our commitment to implement green lighting solutions, to create possibilities for a brighter future and a cleaner planet.



outdoor
flood lighting
page 26



outdoor
landscape lighting
page 28



cleanray
page 30

Modern Workspaces

right light for
cheerful workspaces



OpusLED is elegant, fluidic & modern in design with unique floating spherical diffuser and surrounding light chamber that subtly introduces a circular geometry into the ceiling plane.

OpusLED

LM 38
High efficiency recess mounted LED luminaire




new



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM38-461-XXX-57-XX	34	5700	9,790

VergeLED

LM 29
High efficiency recess mounted versatile LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM29-451-XXX-57-XX	33	5700	6,490
LM29-451-XXX-57RCC	33	5700	7,050
LM29-451-XXX-57GRID	33	5700	7,250

RCC suffix denotes suspension mounting for RCC ceiling.
GRD suffix denotes suspension mounting for modular ceiling.




LIGHT AROUND YOU

VergeLED's minimal design integrates ceiling into the luminaire creating a unique volumetric lighting experience.

ImmaculateLED Trimless

CRCO 10
Recess mounted LED luminaire with minimalist trim and full diffuser



new

Cat No.	System Wattage (W)	CCT (K)	LP (₹)
CRCO10R038HP57SLAB	31	5700	5,950

For all 2x2 products, frame to be ordered separately for installation in POP/gypsum ceiling.
Catalogue no. for frame is 9180P01089 LP Rs. 590 | Cutout dimension: 608 mm x 608 mm.

ImmaculateLED

CRCO 10
Recess/surface mounted LED luminaire with full diffuser



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
CRCO10R038HP57G1	31	5700	5,250
CRCO10S038HP57G1	31	5700	5,650
CRCO10R036HP57G1	33	5700	5,890
CRCO10S036HP57G1	33	5700	6,290

'R' represents recess and 'S' represents surface mounting.

For all available correlated colour temperatures (CCT) and beam angles, LP remains the same. 5

Modern Workspaces • Recessed

ImmaculateLED DD

LM 24

Recess mounted LED luminaire with drop down diffuser



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM24-391-XXX-57-DD	31	5700	5,650
LM24-421-XXX-57-DD	33	5700	6,290

ImmaculateLED Platinum

LM 25

Recess mounted slim LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM25-361-XXX-65-G1*	36	6500	5,950
LM25-481-XXX-65-G1**	36	6500	6,750

Cutout dimensions: *570 mm x 570 mm | **270 mm x 1170 mm

ElateLED

CRCO 10

Recess mounted LED luminaire with full diffuser



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
CRCO10R038HP57GL1	36	5700	5,590

WaveLED

LM 24

Recess mounted LED luminaire




Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM24-391-XXX-57-G1	31	5700	5,750
LM24-421-XXX-57-G1	33	5700	6,390

SpacioLED

LM 15

Recess mounted indirect-direct LED luminaire for new age workspaces



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM15-361-XXX-57-XX	32	5700	4,390
LM15-411-XXX-57-XX	35	5700	4,890

Matrix-ILED

LM 17

Recess mounted LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM17-401-XXX-57-XX	30	5700	4,490
LM17-461-XXX-57-XX	33	5700	4,990

For all 2x2 products, frame to be ordered separately for installation in POP/ gypsum ceiling.
Catalogue no. for frame is 9180P01089 LP Rs. 590 | Cutout dimension: 608 mm x 608 mm.

LED is an ever improving & evolving technology. Wipro is committed to bring you the best in LED technology.



AxeonLED Recess

LM 34
Recess mounted linear
LED luminaire



new

Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM34-251-XXX-57-RM	20	5700	7,890
LM34-251XXX-57RMCT	20	5700	7,890

Cutout dimensions: 1188 mm x 60 mm

AxeonLED Trimless

LM 34
Recess mounted linear
LED luminaire



new

Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM34-251-XXX-57-TL	20	5700	8,390
LM34-251XXX-57TLCT	20	5700	8,390

Cutout dimensions: 1182 mm x 54 mm

Aura Plus

CRCO 13
Recess/surface mounted
LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
CRCO13R038HP57G1	31	5700	6,790
CRCO13S038HP57G1	31	5700	7,290

'R' represents recess and 'S' represents surface mounting.
Frame to be ordered separately for installation in POP/gypsum ceiling.

AxeonLED gives the flexibility to choose as per the requirement of available space, blending well with the modern architecture, delivering value in every aspect.

LineosLED

LM 30
Linear recess mounted LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM30-211-XXX-57-XX	21	5700	5,990
LM30-211-XXX-57-CT	21	5700	6,090
LM30-401-XXX-57-XX	32	5700	6,950
LM30-401-XXX-57-CT	32	5700	7,050

Cutout dimensions: 1178 mm x 78 mm

TZLED

LM 35
Recess mounted slim LED luminaire
suitable for TechZone ceiling



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM35-381-XXX-57-G1	28	5700	8,690
LM35-381-XXX-57-CT	28	5700	8,790
LM35-761-XXX-57-G1	56	5700	17,090
LM35-761-XXX-57-CT	56	5700	17,190

Cutout dimensions: 1178 mm x 133 mm

Modern Workspaces • Suspended

Modern Workspaces

do your offices in style



AxeonLED Drop Down

LM 34

Suspended linear LED luminaire with drop down diffuser



new

Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM34-251-XXX-57-DD	20	5700	8,190
LM34-251XXX-57DDCT	20	5700	8,290
LM34-501-XXX-57-DD	40	5700	16,290
LM34-501XXX-57DDCT	40	5700	16,390

Please order suspension separately.

AxeonLED

LM 34

Linear suspended up-down light, LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM34-361-XXX-57-XX	29	5700	8,750
LM34-361-XXX-57-CT	29	5700	8,850
LM34-721-XXX-57-XX	58	5700	17,050
LM34-721-XXX-57-CT	58	5700	17,150

Please order suspension separately. Order product code with CT for end-to-end installation.

AxeonLED

LM 34

Linear suspended down light, LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM34-251-XXX-57-XX	20	5700	6,990
LM34-251-XXX-57-CT	20	5700	7,090
LM34-501-XXX-57-XX	40	5700	13,890
LM34-501-XXX-57-CT	40	5700	13,990

Please order suspension separately. Order product code with CT for end-to-end installation.

PieLED

LM 78

Linear up-down light suspended LED luminaire



APPLIED FOR DESIGN REGISTRATION

Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM78-401-XXX-57-XX/CT	26	5700	13,090
LM78-801-XXX-57-XX/CT	52	5700	26,190

Please order suspension separately.



Suspension for PieLED and AxeonLED



Universal suspension system with quick onsite adjustment: mounting with 2 nos. suspension from ceiling		LP (₹)
WX 861	Suitable for installation on RCC ceiling	590
LMX 341	Suitable for installation on RCC ceiling	590
WX 862	Suitable for installation on modular grid Armstrong (Prelude 24mm exposed suspension system)	690
WX 863	Suitable for installation on modular grid Armstrong (Silhouette 15mm)	690
LMX 342	Suitable for installation on modular grid Prelude 24mm ceiling system	690
LMX 343	Suitable for installation on modular grid Silhouette 15mm ceiling system	690


Suspension Series: WX86 is for PieLED | LMX34 is for AxeonLED

Modern Workspaces • Suspended

AsimlineLED

LM 77

The slimmest luminaire in class



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM77-441-XXX-57-V1	32	5700	11,290
LM77-441-XXX-40-V1	32	4000	11,290

Please order suspension separately.

LineosLED

LM 31

Linear suspended LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM31-211-XXX-57-XX	21	5700	6,750
LM31-211-XXX-57-CT	21	5700	6,850
LM31-401-XXX-57-XX	32	5700	7,950
LM31-401-XXX-57-CT	32	5700	8,050

Please order suspension separately.

Suspension for AsimlineLED



Universal suspension system with quick onsite adjustment: mounting with 2nos. suspension from ceiling

	LP (₹)
LMX 771 Suitable for installation on RCC ceiling	550
LMX 772 Suitable for installation on modular grid Armstrong Prelude ceiling	650
LMX 773 Suitable for installation on modular grid Armstrong silhouette ceiling	650

Suspension for LineosLED



Universal suspension system with quick onsite adjustment: mounting with 2nos. suspension from ceiling

	LP (₹)
WX 861 Suitable for installation on RCC ceiling	590
WX 862 Suitable for installation on modular grid Prelude 24 mm ceiling system	690
WX 863 Suitable for installation on modular grid Silhouette 15mm ceiling system	690



AxeonLED Surface

LM 34

Surface mounted linear LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM34-251-XXX-57-SM	20	5700	8,290

LH13 LED

LH 13
Pendant mounted LED luminaire with
spun aluminium reflector



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LH13-301-060-40-XX	32	4000	8,790
LH13-301-060-57-XX	32	5700	8,790

OrbitLED

LM 71
Circular suspended fully diffused
LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LM71-341-XXX-40-XX	26	4000	10,290
LM71-441-XXX-40-XX	34	4000	11,850
LM71-341-XXX-57-XX	26	5700	10,290
LM71-441-XXX-57-XX	34	5700	11,850



ComfortLED

LW 04
Wall mounted personal LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LW04-411-XXX-57-XX	31	5700	7,590

Commercial Interiors • Downlighters

Commercial Interiors

create the ambience



HeliosLED

LD 90
High performance recess mounted
LED downlighter



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LD90-111-XXX-65-XX*	9	6500	1,390
LD90-141-XXX-65-XX*	12	6500	1,490
LD90-191-XXX-65-XX**	15	6500	1,590
LD90-231-XXX-65-XX***	18	6500	1,790

Cutout dimensions: *Ø125 mm | **Ø145 mm | ***Ø165 mm

IrisLED

LD 71
Recess mounted circular
LED downlighter



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LD71-111-SMS-65-XX*	11	6500	1,590
LD71-161-SML-65-XX**	15	6500	1,690

Cutout dimensions: *Ø110 mm | **Ø145 mm

HelixLED

LD 91
Recess mounted circular
LED downlighter



new

Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LD91-141-XXX-65-XX	11	6500	1,690
LD91-201-XXX-65-XX	15	6500	1,890

Cutout dimensions: Ø165 mm

IrisLED Gold RF

LD 71
Recess mounted circular LED
retrofit downlighter



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LD71-111-SML-65-RF	11	6500	1,850
LD71-161-SML-65-RF	15	6500	1,950

Cutout dimensions: Ø168 mm

IrisLED Gold FD

LD 71
Recess mounted LED downlighter
with flushed diffuser



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LD71-111-SML-65-FD	11	6500	1,750
LD71-161-SML-65-FD	15	6500	1,850

Cutout dimensions: Ø145 mm

IrisLED Gold DD

LD 71
High efficiency LED downlighter with
drop down diffuser



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LD71-111-SML-65-DD	11	6500	1,750
LD71-161-SML-65-DD	15	6500	1,850

Cutout dimensions: Ø145 mm

Commercial Interiors • Downlighters

IrisLED SQ

LD 74

High efficiency square LED downlighter



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LD74-101-XXX-65-XX*	11	6500	2,090
LD74-121-XXX-65-XX**	14	6500	2,190
LD74-151-XXX-65-XX***	16	6500	2,490

Cutout dimensions: *97 mm x 97 mm | **117 mm x 117 mm | ***137 mm x 137 mm

Halo

CRDL 11

Recess mounted circular LED downlighter



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
CRDL11R008HP57*	6	5700	1,950
CRDL11R013HP57*	9	5700	2,050
CRDL11R017HP57*	12	5700	2,250
CRDL11R023HP57*	18	5700	2,690
CRDL11R033HP57**	26	5700	4,650

Cutout dimensions: *Ø172 mm | **Ø220 mm

Halo

CRDL 11

Surface mounted circular LED downlighter



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
CRDL11S008HP57	6	5700	2,590
CRDL11S013HP57	9	5700	2,690
CRDL11S017HP57	12	5700	2,950
CRDL11S023HP57	18	5700	3,490
CRDL11S033HP57	26	5700	5,790

SpherisLED

CRDL 10

Recess mounted circular LED downlighter



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
CRDL10R005HP60*	6	6000	990
CRDL10R010HP60**	11	6000	1,390
CRDL10R015HP60***	17	6000	1,790

Cutout dimensions: *Ø90 mm | **Ø115 mm | ***Ø140 mm



LED is an ever improving & evolving technology. Wipro is committed to bring you the best in LED technology.



LED Gimball

LD 56
Circular gimball luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LD56-251-060-40-XX*	20	4000	3,850
LD56-381-060-40-XX**	32	4000	5,150
LD56-501-060-40-XX**	41	4000	4,450

Also available in beam angles: 16°, 24°, 36°
Cutout dimensions: *Ø115 mm | **Ø135 mm

LED Gimball

LD 58
Square gimball luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LD58-251-060-40-XX*	20	4000	3,850
LD58-381-060-40-XX**	32	4000	5,150
LD58-501-060-40-XX**	41	4000	4,450

Also available in beam angles: 16°, 24°, 36°
Cutout dimensions: *95 mm x 95 mm | **135 mm x 135 mm | ***150 mm x 150 mm
Available in twin & triple head options.

LED Swivel Projector

LD 59
Circular adjustable/rotatable
downlight luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LD59-251-036-40-XX*	20	4000	5,490
LD59-381-036-40-XX**	32	4000	6,590
LD59-501-036-40-XX**	41	4000	9,250

Also available in beam angles: 16°, 24°, 60°
Cutout dimensions: *Ø110 mm | **Ø140 mm | *** Ø165 mm

LED Tracklight

LD 57
LED Track Light



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LD57-251-036-40-XX	20	4000	4,950
LD57-381-036-40-XX	32	4000	5,250
LD57-501-036-40-XX	41	4000	6,290

Also available in beam angles: 24°, 60°
Please order suitable accessories as below.

Cat No.		LP (₹)
XTS-5100	Single phase 1 mtr track	1,190
XTS-5200	Single phase 2 mtr track	2,390
XTS 52	Straight connector	290
SKB520	2 mtr single suspension	590



For all available correlated colour temperatures (CCT) and beam angles, LP remains the same. 15

Lighting Controls

Lighting Controls

cost, convenience & comfort



eSavvy

CRPS 10
Smart PIR occupancy sensor



Cat No.		LP (₹)
CRPS10R010A	Passive Infrared Sensor	4,090

Cutout dimensions: Ø72 mm

eSavvy

CRPS 13
PIR sensor switching photocell



Cat No.		LP (₹)
CRPS13R010A	Programmable Occupancy Sensor	5,990

Cutout dimensions: Ø72 mm

eSavvy

CRAD
High performance programmable PIR
occupancy sensor with daylight dimming



Cat No.		LP (₹)
CRADDPS10R010A	Occupancy sensor with daylight dimming suitable for 1-10V analogue ballast	8,090

Cutout dimensions: Ø72 mm

eSense

COM 20/CDA 21
High performance programmable PIR
occupancy sensor with daylight dimming



Cat No.		LP (₹)
COM 20010	Occupancy sensor	14,990
CDA 21010	Occupancy sensor with daylight dimming suitable for 1-10V analogue ballast	16,890

Cutout dimensions: Ø60 mm

eSense

COM 23/CDA 24
High performance microwave occupancy
and daylight dimming sensors



Cat No.		LP (₹)
COM 23010	Occupancy sensor	12,590
CDA 24010	Occupancy sensor with daylight dimming suitable for 1-10V analogue ballast	13,590

Cutout dimensions: Ø60 mm

eSense

CRADSS11/CRADSS12
CRADSS13
Scene select system



4 channel scene select

Cat No.		LP (₹)
CRADSS11R010A	1 channel scene select	29,990
CRADSS12R020A	2 channel scene select	50,990
CRADSS13R040A	4 channel scene select	91,690



Cleanroom & Sterile areas

Cleanroom & Sterile Areas

clean and pure light for
zero error zones



VisionLED BOCR

LC 20

Recess mounted, bottom opening
cleanroom LED luminaire




Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LC20-411-XXX-57-XX*	30	5700	8,150
LC20-551-XXX-57-XX**	42	5700	9,350
LC20-721-XXX-57-XX**	60	5700	10,750

Cutout dimensions: *490 mm x 490 mm | **580 mm x 580 mm

VisionLED Prime TOCR

LC 30

Best-in-class top opening
cleanroom luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LC30-411-XXX-57-G1	30	5700	9,550
LC30-551-XXX-57-G1	42	5700	10,290
LC30-721-XXX-57-G1	60	5700	10,990
LC30-102-XXX-57-G1	78	5700	14,390
TFTC100*	-	-	4,190


*Top frame & top cover (TFTC) to be ordered separately.

Cutout dimensions: 600 mm x 600 mm

VisionLED Retrofit

HC 30

Suitable for retrofit solution



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
HC30-411-XXX-57-XX	31	5700	6,590
HC30-551-XXX-57-XX	42	5700	8,990



Leaders in cleanroom lighting

Dedicated team of cleanroom lighting specialists

VisionLED range is designed and developed by technical experts with a sound understanding of a cleanroom

Conformity to international standards

VisionLED range conforms to international guidelines for USFDA - Food and Drug Administrative Procedures and GMP - Good Manufacturing Practices

Design and develop customised solutions

Over the years, we have designed and developed more than 750 customised product variants catering to the ever-evolving needs of Pharmaceutical, Food & Beverages and Electronics & Semi Conductor Industries

More than 20 years of experience

Today, most leading companies choose VisionLED luminaires as the preferred choice for their cleanrooms

Over 2000 successful installations

With as many as 2000 successful installations, VisionLED is uniquely positioned as the leader in cleanroom lighting

For any queries on cleanroom lighting applications, contact our nearest branch or write to helpdesk.lighting@wipro.com

Industries

Industries

enhanced efficiency with
effective savings



XpressbayLED

LH 15
Linear LED highbay suspended luminaire



new

Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LH15-102-060-57-XX	75	5700	16,990
LH15-142-060-57-XX	100	5700	21,990
LH15-182-060-57-XX	130	5700	29,990
LH15-282-060-57-XX	200	5700	43,990

Also available in 90° beam angle.
Please order suspension separately.

RadialLED Prime

LH 09
Integral SMD LED highbay luminaire with aluminium reflector



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LH09-102-060-50-G1	80	5000	13,490
LH09-122-060-50-G1	100	5000	16,990
LH09-172-060-50-G1	140	5000	20,190
LH09-232-060-50-G1	200	5000	25,290

Also available in 100° beam angle.

Wellglass Luminaire

LE 02
IP65 LED wellglass luminaire



new

Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LE02-441-XXX-57-OP	35	5700	5,500
LE02-821-XXX-57-OP	70	5700	7,500

Also available in clear glass and glass with mesh.

Canopy Luminaire

LH 14
High efficiency LED mid/highbay canopy luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LH14-102-XXX-57-XX	80	5700	12,590
LH14-192-XXX-57-XX	150	5700	23,590

RadialLED

LH 09
Rugged LED midbay and highbay for varied industrial applications



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LH09-851-060-50-V5	65	5000	12,690
LH09-921-060-50-V5	80	5000	14,890
LH09-132-060-50-V5	100	5000	18,690
LH09-122-060-50-V5	120	5000	20,390
LH09-192-060-50-V5	135	5000	22,190
LH09-212-060-50-V5	165	5000	26,090
LH09-262-060-50-V5	200	5000	29,990

Also available in 90° beam angle.

StormLED

LE 02
IP65 high efficiency LED wellglass




Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LE02-391-XXX-65-XX	29	6500	5,150
LE02-521-XXX-65-XX	40	6500	5,590

Industries

XlineLED Pro

LE 14
IP54 trunk mounted LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LE14-491-XXX-57-XX	39	5700	7,790

Please order trunk separately.

Trunk for XlineLED Pro

Trunk pre-wired with internal wiring and suspension system

Cat No.	Length	LP (₹)
LE14A02C	1.2 mtr extruded aluminium	2,190

XlineLED

LE 11
Trunk mounted LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LE11-491-XXX-57-XX	39	5700	4,250

Please order trunk separately.

Trunk for XlineLED

Trunk pre-wired with internal wiring and suspension system

Cat No.	Length	LP (₹)
WCX21770	1.77 mtr	2,390
WCX23540	3.54 mtr	4,190



XlineLED

LE 10
Industrial integral LED channel



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LE10-491-XXX-57HCSL	39	5700	4,250

CapsuleLED

LE 20
Surface/pendant mounted
totally enclosed LED luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LE20-491-XXX-57-XX	39	5700	5,350



Outdoor • Street Lighting

Street Lighting

safe and vibrant outdoors



SkylineLED

LR 02
High performance IP66 LED streetlight



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LR02-291-XXX-57-XX	25	5700	3,090
LR02-331-XXX-57-XX	30	5700	3,390

SkylineLED

LR 02
High performance IP66 LED streetlight



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LR02-451-XXX-57-G1	40	5700	5,990
LR02-501-XXX-57-G1	45	5700	6,290

SkylineLED

LR 02
High performance IP66 LED streetlight



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LR02-391-XXX-57-XX	35	5700	5,590
LR02-451-XXX-57-XX	40	5700	6,390
LR02-501-XXX-57-XX	45	5700	6,690

SkylineLED

LR 02
High performance IP66 LED streetlight



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LR02-671-XXX-57-XX	60	5700	8,890
LR02-781-XXX-57-XX	70	5700	9,190
LR02-981-XXX-57-XX	80	5700	11,090
LR02-102-XXX-57-XX	90	5700	11,490
LR02-112-XXX-57-XX	100	5700	11,890
LR02-122-XXX-57-XX	110	5700	12,390
LR02-132-XXX-57-XX	120	5700	16,090

SkylineLED

LR 02
High performance IP66 LED streetlight



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LR02-172-XXX-57-XX	135	5700	16,790
LR02-182-XXX-57-XX	150	5700	23,590
LR02-212-XXX-57-XX	180	5700	26,890
LR02-242-XXX-57-XX	200	5700	28,290
LR02-262-XXX-57-XX	220	5700	28,790
LR02-292-XXX-57-XX	250	5700	31,890



Outdoor • Flood Lighting

Flood Lighting

safe and vibrant outdoors





AlphaLED Floodlight

LF 19
LED floodlight luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LF19-711-060-57-XX	60	5700	9,590
LF19-931-060-57-XX	80	5700	10,890

AlphaLED Floodlight

LF 20
LED floodlight luminaire



new

Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LF20-122-060-57-XX	100	5700	14,790
LF20-132-060-57-XX	120	5700	15,590
LF20-192-060-57-XX	150	5700	20,490

AlphaLED Floodlight

LF 20
LED floodlight luminaire



new

Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LF20-272-060-57-XX	200	5700	29,390
LF20-342-060-57-XX	250	5700	38,590
LF20-392-060-57-XX	300	5700	45,990
LF20-442-060-57-XX	350	5700	48,990

RevoLED Floodlight

LF 07
High efficiency LED floodlight luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LF07-102-060-50-V5	100	5000	18,290
LF07-122-060-50-V5	120	5000	18,790
LF07-152-060-50-V5	150	5000	28,890
LF07-282-060-50-V5	200	5000	31,390
LF07-272-060-50-V5	250	5000	41,490
LF07-472-060-50-V5	350	5000	52,990
LF07-582-060-50-V5	415	5000	59,990

Also available in beam angle: 90° | Please order appropriate beam angle after discussion with Wipro team.



Landscape Lighting

redefine landscapes with
better light quality





UrbanoLED Pathway

LP 05
IP66 LED pathway luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LP05-711-XXX-65-XX	60	6500	39,990

UrbanoLED Pathway

LP 06
IP66 LED pathway luminaire



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LP06-351-XXX-57-XX	35	5700	23,190

Post TopLED

LP 02
IP65 aesthetically appealing
vintage LED post top



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LP02-501-XXX-57-XX	45	5700	13,290

FantasyLED Bollard

CRLA 11
IP65 LED bollard suitable for
landscape lighting



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
CRLA11008HP57-05	8	5700	6,990
CRLA11008HP57-08	8	5700	7,090

GardeniaLED

LF 05
IP67 integral LED bushlight



Cat No.	System Wattage (W)	CCT (K)	LP (₹)
LF05-450-024-27-XX	6	2700	5,090
LF05-450-036-27-XX	6	2700	5,090
LF05-450-055-27-XX	6	2700	5,090
LF05-600-024-27-XX	8	2700	5,890
LF05-600-036-27-XX	8	2700	5,890
LF05-600-055-27-XX	8	2700	5,890



Cleanray

Cleanray

range of energy efficient and
high performance led luminaires



ElateLED

CRCO 10

Recess mounted LED luminaire with complete diffuser



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
CRCO10R038HP57GL	36	5700	4,790

Frame to be ordered separately for installation in POP/gypsum ceiling.
Catalogue no. for frame is 9180P01089 LP Rs. 590 | Cutout dimension: 608 mm x 608 mm

ImmaculateLED Slim

CRCO 23

Recess mounted slim LED luminaire



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
CRCO23R036HP65G1	36	6500	4,590

Frame to be ordered separately for installation in POP/gypsum ceiling.
Catalogue no. for frame is 9180P01089 LP Rs. 590 | Cutout dimension: 608 mm x 608 mm

IrisLED Slim RO

LD 80

Recessed mounted round slim panel LED downlighter



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
LD80-200-XXX-60-XX*	3	6000	490
LD80-350-XXX-60-XX**	6	6000	890
LD80-530-XXX-60-XX***	9	6000	950
LD80-101-XXX-60-XX****	12	6000	1,250
LD80-131-XXX-60-XX*****	15	6000	1,350
LD80-171-XXX-60-XX*****	18	6000	2,050

Cutout dimensions: *Ø75 mm | **Ø108 mm | ***Ø135 mm | ****Ø157 mm | *****Ø178 mm |
*****Ø205 mm

IrisLED Slim SQ

LD 81

Recess mounted square slim LED luminaire



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
LD81-200-XXX-60-XX*	3	6000	490
LD81-350-XXX-60-XX**	6	6000	890
LD81-530-XXX-60-XX***	9	6000	950
LD81-101-XXX-60-XX****	12	6000	1,250
LD81-131-XXX-60-XX*****	15	6000	1,350
LD81-171-XXX-60-XX*****	18	6000	2,050
LD81-200-XXX-60-XX*****	24	6000	3,290

Cutout dimensions: *75 mm x 75 mm | **108 mm x 108 mm | ***135 mm x 135 mm
****157 mm x 157 mm | *****178 mm x 178 mm | *****205 mm x 205 mm |
*****279 mm x 279 mm

IrisLED Slim RO/SQ SM

LD 80/81

Surface mounted round/square slim panel LED downlighter



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
LD80-350-XXX-60-SM	6	6000	1,050
LD80-101-XXX-60-SM	12	6000	1,490
LD80-171-XXX-60-SM	18	6000	2,390
LD81-350-XXX-60-SM	6	6000	1,050
LD81-101-XXX-60-SM	12	6000	1,490
LD81-171-XXX-60-SM	18	6000	2,390

SquarisLED

CRDL 15
Recess mounted square slim
LED luminaire



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
CRDL15R005HP60*	6	6000	990
CRDL15R010HP60**	11	6000	1,390
CRDL15R015HP60***	17	6000	1,790

Cutout dimensions: *90 mm x 90 mm | **115 mm x 115 mm | ***140 mm x 140 mm

SlimrisLED

CRDL 14
Recess mounted circular
slim LED luminaire




Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
CRDL14R005HP60*	6	6000	990
CRDL14R010HP60**	11	6000	1,390
CRDL14R015HP60***	17	6000	1,790

Cutout dimensions: *Ø90 mm | **Ø115 mm | ***Ø140 mm

TrimLED NEO

LL 20
LED batten suitable for
indoor applications



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
LL20-111-XXX-65-NE	10	6500	550
LL20-221-XXX-65-NE	18	6500	850

TrimLED

LL 20
High efficiency LED
aluminum linear batten



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
LL20-281-XXX-65AL1	20	6500	1,390

new

ProLED

LL 13
High efficiency LED linear lamp



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
LL13-181-650	18	6500	990
LL13-181-65SE	20	6500	1,150

ProLED T5

LL 13
High efficiency LED linear T5 lamp




Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
LL13-181-65-T5	18	6500	1,290

new



ProLED Compact

LL 18
High efficiency LED compact lamp



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
LL18-181-65PL	18	6500	1,050

WIOLED

WIO 92
Channel suitable for ProLED lamp



Cat No.	System Wattage (W)	MRP (₹)
WIO 921208	Single 4 feet LED lamp	490
WIO 922208	Twin 4 feet LED lamp	590

Please order suitable ProLED tube separately.

SkylineLED

LR 02
High performance IP66 LED streetlight



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
LR02-261-XXX-57-XX	20	5700	2,550

FormzLED

LS 06
IP20 non-integral flexible LED striplight



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
LS06-005-120-WH-50	5	-	1,590
LS06-005-120-WW-50	5	-	1,590
LS06-015-120-WH-50	15	-	2,290
LS06-015-120-WW-50	15	-	2,290
LG40-024	-	-	790
LG40-078	-	-	1,490

*LG40-024 - 1 unit is suitable for 1 no (5m spool) of LS06-005 | **LG40-78 - 1 unit is suitable for 1 no (5m spool) of LS06-15 | *Order drive separately. Driver is for indoor use only.

AlphaLED Floodlight

LF 19
Integral high performance LED floodlight



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
LF19-471-060-57-XX	40	5700	7,090

MoonLED

LW 01/02
Circular/square LED wall/ceiling light



Cat No.	System Wattage (W)	CCT (K)	MRP (₹)
LW01-101-XXX-57-XX*	9	5700	2,350
LW02-101-XXX-57-XX**	9	5700	2,350

Frame dimensions: *Ø210 mm | **270 mm x 270 mm

For all available correlated colour temperatures (CCT) and beam angles, MRP remains the same. 33

Items to be phased-out (available till stocks last)

Series	Cat No.	List price (₹)
TuboLED	LM70-421-XXX-57-XX	11,350
	LM70-421-XXX-WW-XX	11,350
Suspension for TuboLED	WVX501	590
	WVX502	690
	WVX503	690
RetroLED	LM75-301-XXX-40-XX	11,790
eSense	CSC2202 + CDX2202	on request
	CIC01	on request
	CCX01	on request
SkylineLED	LR02-171-XXX-57-XX	3,350

Terms and conditions

- Prices are in Indian rupees.
- LP/MRP are inclusive of GST. However authorized Wipro sales person/stockists can sell below the LP/MRP.
- All prices are subject to Wipro's general terms & conditions of business.
- Prices are subject to change without notice as per company discretion.
- This price list supersedes all earlier price lists.
- Company reserves the right to issue amendments, which may arise due to any errors in the price list.
- Goods are dispatched by us on purchaser's risk. All claims for loss, damage or shortage will be filed by the purchasers directly with the carriers.
- Orders should be placed in multiples of case lot.
- All orders shall be placed in writing.
- Items other than those included in the price list, stands phased out from the range.
- All fixtures will be supplied as per our normal specifications, for additional features please contact nearest Wipro office for details.
- Disputes, if any are subject to Pune jurisdiction only.

Innovation and improvement are a way of life at Wipro. All rights reserved.
Reproduction of this data in part or in whole without permission is prohibited.
Care has been taken to ensure that the information content within is correct.
We reserve the right to modify the product without prior intimation.
Photographs shown herein are indicative.
Customers are advised to reconfirm the data or product dimensions before purchase with our local office.



Branch Offices

E-40/7, Okhla Industrial Area, Phase-II,
New Delhi - 110 020
Tel: 011-4170 8121/29

No.139, 7th Cross, N S Palya, off. Bannerghatta Road,
Bangalore - 560 076
Tel: 080-4150 3260

3, Pretoria Street, 3rd floor,
Kolkata - 700 071
Tel: 033-4404 5886/87

Plot No.,13 A/1, Road No. 9, IDA East Division Nacharam, R.R.Dist.,
Hyderabad - 500 076
Tel: 040-2717 6082

1401/1402, 14 Floor, C-wing Lotus Corporate Park, Goregaon (East)
Mumbai - 400 083
Tel: 022-6218 2000

Economist House, S-15, First Cross Road,
Thiru Vi Ka Industrial Estate, Guindy
Chennai - 600 032
Tel: 95660 86333

Bhosale Heights, 1195/5, Fergusson College Road,
Pune - 411 005
Tel: 020-2553 5081

S.C.O. - 208 - 209, 3rd Floor Sector - 34 A,
Chandigarh - 160 022
Tel: 0172-5001 8734

E/149, Transport Nagar, Lucknow Kanpur Road,
Lucknow - 226 012
Tel: 0522-2434 352

H-409, Titanium City Centre, 100 ft. Road, Anand Nagar
Ahmedabad - 380 015
Tel: 079-4007 3546

Khasra No.48.49/2, khedia Business Park, Tatibanth
Raipur (CG) - 492 099
Tel: 0771-3265 725

1-99, Sirigudi Nagar, Yendada
Vishakhapatnam - 530 045
Tel: 96769 08080/99449 825284

No.41, Chokkampudur Main Road, Sriram Nagar, Telungupalayam Post,
Coimbatore - 641 039
Tel: 98947 95836

B - 16/17, Palsania Complex, Near T B Hospital,
Subhash Nagar Shopping Centre,
Jaipur - 320 016
Tel: 0141-2280 014/4910 879

311, Pujer Complex, Subhanpura,
Baroda - 390 023
Tel: 0265-2395 830/35/36/41/45

United Compound, A.B. Road, Dewas Naka,
Indore (MP) - 452 010
Tel: 98279 99668

Hindustan Associates, Plot no. 135,
Mancheshwar Industrial Estate, Rasulgarh,
Bhubaneshwar - 751 010
Tel: 0674-6450 804

Flat No. 8, Plot No. 191, 1st Floor, Rachna Apartment,
Cement Road, Shivaji Nagar,
Nagpur - 440 010
Tel: 0712-2569 878

VI/409-D, Valomkottil Building,
Opp. BMC, Sea Port-Air Port Road, P.O. Thrikkakkara,
Cochin - 682 021
Tel: 98957 08464

Wipro Lighting Advantage

Innovative lighting solutions for indoor and outdoor applications through:

- Energy saving solutions with latest international technologies
- Capability to service multi-locational accounts
- Service commitment: 19 branches and over 350 dedicated stockists
- Ease of contact through website
- Trustworthiness and reliability of Wipro



Scan the QR code to download the app



Business Office:

Wipro Lighting, 5th floor, Godrej Eternia - C,
Old Pune-Mumbai Highway, Shivajinagar, Pune - 411 005
Tel: 020-66098700, Fax: 020-66098777
E-mail: helpdesk.lighting@wipro.com

Registered Office:

Wipro Enterprises (P) Limited , 'C' Block, CCLG Division,
Doddakannelli, Sarjapur Road, Bangalore - 560035, India.

Toll-free no: 1800-425-1969

www.wiprolighting.com

Follow us on [LinkedIn](#)

Authorised Stockist