

**POLYCAB WIRES PVT. LTD.**

Industrial Cables LP No. 03/2017-18 Dtd 1st August 2017

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT (FR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FR							
	45 Mtr.	Coils Per Box	90 Mtrs.	Coils Per Box	180 Mtrs. (Box Packing)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box
0.75	390	48	740	28			2465	10
1	505	36	965	24	1930	12	3215	8
1.5	760	30	1445	16	2890	10	4815	6
2.5	1210	20	2305	12	4610	6	7685	4
4	1815	16	3455	8	6910	4	7680	4
6	2690	8	5125	6	10250	3	11390	3
10			9065	1			20145	1
16			14530	1			32290	1

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – FLAME RETARDANT LOW SMOKE (FRLSH) /FLAME RETARDANT ZERO HALOGEN (FRZH) / LOW SMOKE ZERO HALOGEN (LSZH) / HALOGEN FREE FLAME RETARDANT (HFFR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FRLS				HFFR/FRZH/LSZH	
	180 Mtrs. (Box Packing)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box
0.75			2605	10	2825	10
1	2025	12	3375	8	3680	8
1.5	3035	10	5060	6	5500	6
2.5	4845	6	8075	4	8790	4
4	7275	4	8085	4	8615	4
6	10725	3	11920	3	12695	3
10			21210	1	22595	1
16			34060	1	36280	1

Notes

1. The above rates are exclusive of GST which shall be charged extra.
2. This Price List is subject to change without notice.
3. As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.