



POLYCAB WIRES PVT. LTD.

PCC LP NO. 4 /2017-18 Dtd : 22nd August 2017

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Armoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWay / A2XFay	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		67	72		84
4		71	78		90
6		83	91		103
10		99	115		131
16	65	116	123		146
25	78	119	155	174	188
35	94	146	196	220	244
50	114	183	247	286	316
70	145	243	333	388	428
95	164	313	414	470	522
120	197	373	495	586	640
150	234	450	610	694	787
185	286	560	745	866	978
240	351	729	954	1090	1248
300	427	889	1152	1336	1504
400	536	1119	1465	1700	1912
500	734	1480	1984	2312	2595
630	858	1864	2631	3141	3511
800	1183				
1000	1363				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Round Wire Armouring	
- 2 x 16 & above	25%
- 3 x 16 & 3.5CX25 & above	25%
- 4 x 10 & above	25%
- For Single core 95 & above	25%
b) Stranding 10 sq.mm and below	10%
c) Extruded PVC Innersheath Up 50	5%
Extruded PVC Innersheath 70 & Above	2.5%
d) HR PVC Insulation	10%
e) HR PVC Inner Sheath	5%
f) HR PVC Outer Sheath	5%
g) Oxygen Index (FR)	2.5%
h) PVC Insulated Cables	8%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
		Power (Al.)		
Upto 16	10%	7.5%	15%	20%
25 - 50	7.5%	7.5%	12.5%	15%
70 & above	5%	5.0%	15%	12.5%
		Power Single Core (Al.)		
Upto 16	-N.A-	10%	-N.A-	25%
25 - 50	-N.A-	10%	-N.A-	20%
70 & above	-N.A-	7.5%	-N.A-	17.5%

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB WIRES PVT. LTD.

PCC LP NO. 4 /2017-18 Dtd : 22nd August 2017

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Unarmoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		46	49		55
6		52	59		70
10		62	76		92
16	36	76	98		120
25	47	98	133	153	163
35	58	124	170	194	215
50	76	158	223	258	283
70	101	213	309	356	395
95	138	285	382	442	495
120	172	340	472	555	616
150	209	414	585	669	765
185	257	517	727	842	951
240	322	686	929	1072	1217
300	395	847	1143	1319	1489
400	518	1086	1436	1663	1878
500	616	1366	1871	2161	2439
630	725	1723	2478	2930	3291
800	1030				
1000	1211				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Stranding 10 sq.mm and below	10%
b) Extruded PVC Innersheath Up 50	5%
Extruded PVC Innersheath 70 & Above	2.5%
c) HR PVC Insulation	10%
d) HR PVC Inner Sheath	5%
e) HR PVC Outer Sheath	5%
f) Oxygen Index (FR)	2.5%
g) PVC Insulated Cables	8%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath Unarmd.	Inner Sheath	Outer Sheath
Power (Al.)				
Upto 16	10%	7.5%	15%	20%
25 - 50	7.5%	7.5%	12.5%	15%
70 & above	5%	5%	15%	12.5%
Power Single Core (Al.)				
Upto 16	-N.A-	10%	-N.A-	25%
25 - 50	-N.A-	10%	-N.A-	20%
70 & above	-N.A-	7.5%	-N.A-	17.5%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB WIRES PVT. LTD.

PCC LP NO. 4 /2017-18 Dtd : 22nd August 2017

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		126	163	207	272	327	381
6		169	225	289	377	442	525
10		255	343	442	654		
16	179	365	486	638	877		

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XWY/2XFY		Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	74	97	14	306	425
3	90	122	16	316	479
4	108	152	19	367	561
5	127	182	24	459	703
6	145	211	27	512	783
7	161	239	30	587	903
8	182	269	37	715	1101
10	233	314	44	868	1363
12	269	369	61	1186	1857

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	2.50%
D) Round Wire Armouring	
1C x 95 sq. mm & above	7.50%
1.5 sq.mm - 12 core & above	15%
2.5 sq.mm - 9 core & above	15%
10 sq.mm - 4 core & above	15%
16 sq.mm - 2 core & above	15%
16 sq.mm - 3 core & above	15%
E) OXYGEN INDEX (FR)	2.50%
F) HR PVC Insulatoin	7%
HR I/S & O/S	5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	7.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	4%
H) PVC Insulated Cables	5%

Cores	FRLS Loading Factor- Control Cable		LSZH	
	Inner Sheath	Outer Sheath Armoured	Inner Sheath	Outer Sheath
2 to 4 Core	5%	6%	15%	15%
5 to 10 Core	5%	4%	15%	15%
12 & Above	5%	4%	12.50%	12.50%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB WIRES PVT. LTD.

PCC LP NO. 4 /2017-18 Dtd : 22nd August 2017

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core
	2XY	2XY	2XY	2XY
4		102	143	185
6		144	204	267
10		228	320	421
16	165	325	475	627

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	52	74	14	248	386
3	66	96	16	281	442
4	82	123	19	331	521
5	98	146	24	418	656
6	115	174	27	468	733
7	130	200	30	535	840
8	151	229	37	654	1030
10	182	282	44	775	1238
12	215	334	61	1067	1702

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	2.5%
D OXYGEN INDEX (FR)	2.5%
E) HR PVC Insulation	7%
HR PVC I/S & O/S	5% Each
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	7.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	4%
G) PVC Insulated Cables	5%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
Unarmd				
2 - 4	5%	6%	15%	15%
5 - 10	5%	4%	15%	15%
12 & Above	5%	4%	12.5%	12.5%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB WIRES PVT. LTD.

PCC LP NO. 4 /2017-18 Dtd : 22nd August 2017

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	301	568	815	981	1073	1465
35	408	777	1122	1287	1479	2024
50	552	1055	1529	1787	2025	2770
70	777	1494	2170	2529	2900	
95	1092	2145	3117	3642	4173	
120	1373	2689	3918	4667	5252	
150	1708	3355	4890	5640	6555	
185	2101	4127	6018	7035	8061	
240	2699	5308	7752	9036	10391	
300	3364	6611	9651	11257	12947	
400	4407	8667	12665	14645	16987	
500	5562					
630	7000					
800	8869					
1000	11071					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	
25	260	510	764	922	1010	
35	359	706	1056	1216	1400	
50	491	966	1449	1696	1920	
70	699	1373	2070	2413	2769	
95	939	1911	2874	3357	3850	
120	1184	2405	3618	4308	4858	
150	1479	3001	4524	5216	6072	
185	1822	3699	5573	6519	7479	
240	2348	4770	7193	8386	9653	
300	2926	5950	8969	10461	12041	
400	3847	7811	11778	13628	15820	
500	4858					
630	6119					
800	7766					
1000	9702					

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	2.50%
D) Round Wire Armouring	
1C x 95 sq. mm & above	7.50%
10 sq.mm - 4 core & above	15%
16 sq.mm - 2 core & above	15%
16 sq.mm - 3 core & above	15%
E) OXYGEN INDEX (FR)	2.50%
F) HR PVC Insulatoin	7%
HR I/S & O/S	5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	4%
H) PVC Insulated Cables	5%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB WIRES PVT. LTD.

PCC LP NO. 4 /2017-18 Dtd : 22nd August 2017

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

3 Core HT Cables

	(Rate in Rs. Per Mtr.)						
Size in Sq.mm.	3.3 KV (E) / 3.3 KV (UE)	6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35			510				
50			576				
70	600	642	685				
95	727	763	811	1048	1091	1454	
120	855	891	935	1218	1245	1659	
150	965	1005	1044	1346	1373	1757	2086
185	1137	1159	1215	1505	1539	1940	2310
240	1347	1403	1458	1771	1804	2219	2619
300	1592	1673	1696	2037	2069	2493	2922
400	1935	2093	2131	2394	2437	2886	3359
EXTRA FOR SPECIAL CONSTRUCTION:							
1) Extruded PVC Inner Sheath		3%					
2) Pressure Extruded PVC Innersheath		13%					
3) Round Wire Armouring - Up to 11 KV (E)		25%					
11 KV (UE) & Above		27.5%					
4) FRLS PVC Inner Sheath		5%					
5) FRLS PVC Outer Sheath		5%					
6) FR Sheath with Oxygen Index		3%					
<ul style="list-style-type: none"> The above rates are exclusive of GST which shall be charged extra. This cancels all our previous Price Lists. This Price List is subject to change without prior notice. 							



POLYCAB WIRES PVT. LTD.

PCC LP NO. 4 /2017-18 Dtd : 22nd August 2017

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable confirming to IS 7098 / (PART-II) 1985 with latest amendments.

1 Core HT Cables

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	3.3 KV (E) / 3.3 KV (UE)		6.6 KV (E)		6.6 KV (UE) / 11 KV (E)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
25						
35					216	227
50					239	251
70	250	263	256	270	273	286
95	283	298	286	301	303	319
120	319	336	322	339	342	361
150	356	375	360	380	376	397
185	410	432	420	442	451	475
240	506	532	516	543	568	596
300	586	617	602	634	663	699
400	702	739	730	768	793	834
500	884	931	927	976	960	1011
630	1097	1154	1115	1174	1145	1206
800	1359	1430	1371	1442	1390	1463
1000	1639	1725	1645	1731	1808	1904

EXTRA FOR SPECIAL CONSTRUCTION:

1) FRLS PVC Inner Sheath	7.5%				
2) FRLS PVC Outer Sheath	5%				
3) Oxygen Index	3%				

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB WIRES PVT. LTD.

PCC LP NO. 4 /2017-18 Dtd : 22nd August 2017

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

1 Core HT Cables

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	11 KV (UE)		22 KV (E)		33 KV (E)		33 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
25								
35								
50								
70								
95	395	416	411	433	548	576		
120	457	480	462	486	603	635		
150	495	521	503	529	629	663	746	785
185	574	605	589	619	700	736	817	860
240	661	695	677	712	791	833	970	1021
300	744	783	761	802	927	976	1070	1126
400	881	927	901	948	1060	1115	1223	1287
500	1101	1158	1101	1158	1301	1370	1412	1487
630	1307	1375	1307	1375	1525	1605	1652	1739
800	1526	1606	1526	1606	1747	1838	1986	2090
1000	1986	2090	1986	2090	2129	2235	2281	2402

EXTRA FOR SPECIAL CONSTRUCTION:

1) FRLS PVC Inner Sheath	5%							
2) FRLS PVC Outer Sheath	5%							
3) Oxygen Index	3%							

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.